

## 12W Surface Mounted Dimmable LED Downlight



100-240V	12W rated 13W w/driver	 COB LED			OPAQUE 93° BEAM ANGLE	CLEAR 41° BEAM ANGLE	CRI >80	POWER FACTOR 0.98	CONSTANT CURRENT 280mA
----------	------------------------------	--	---	---	--------------------------------	-------------------------------	------------	-------------------------	------------------------------

### Features:

- A quality downlight that is easy to install, especially on hard to cut surfaces like concrete ceilings.
- Includes 2 diffusers (Clear and Opaque)
- COB LED technology for superior light output
- High-grade diecast alloy housing, steel bracket and aluminium heatsink
- SAA approved integrated dimmable LED driver
- Long lasting up to 30,000 hours.
- It's easy to install and perfectly replacing the traditional lighting.
- The products have been tested compatible with most Australia different brand dimmers.

### Dimension:



## Technical Parameters:

Code	DL1113
Input Voltage (V)	100-240V
Shape Color	White / Black
Product size (mm)	Dia. 105mm * H140mm
Installation ways	Surface mounted
Power (W)	12W
Beam angle	100 degree Opaque Diffuser , 40 degree Clare Diffuser
Dimmable	YES
PF	0.95
Efficacy (lm/W)	80LM/W
LUMENS:	WW 850LM CW 900LM
LAMP:	COB LED
CCT (K)	3000K / 4200K / 5000K / 6500K
CRI	82
Material	aluminium body + PC Diffuser
Operating Temperature	-20℃ to 40℃
Certification	SAA/ C-Tick / CE / ROHS
IP Rating	IP20
Warranty	2 Years

## Installation Instruction:

